


# INTERSTELLAR DATA-HUB

## Dimensions




**Metric:**
160 x 90 x 260 mm [X x Y x Z]
**Imperial**
6.30 x 3.55 x 10.24 in [X x Y x Z]

## Technical Data

| | |
|---|---|
| Housing | Polycarbonate |
| Housing Color | RAL 7001 Silver gray |
| Power Consumption | max. 10 W |
| Internal power supply | 100 - 264 VAC (50 - 60 Hz) |
| Protection Class | I |
| Environment | Indoor, Outdoor |
| Ingress protection rating | IP66 |
| Humidity | 0 to 95%, non-condensing |
| Ambient temperature (Operation) | -40 °C to 40 °C \| -40 °F to 104 °F |
| Ambient temperature (Storage) | 5 °C to 40 °C \| 41 °F to 104 °F |
| Ambient temperature (Start-up process) | -25 °C to 40 °C \| -13 °F to 104 °F |
| Impact protection rating | IK08 |
| Approbation | CE |
| Weight | 1.6 kg |

Designed and Developed in Bavaria.
Made in Germany.

sales@biontechnologies.com
www.biontechnologies.com

Phone:
(DE) +49 8231 95787 0



All information without guarantee. Errors, changes and misprints excepted.

# INTERSTELLAR DATA-HUB

## Configurator

IDH - (1) -Y01

| 1 Protocol / Signal | |
|---|---|
| DMX | DMX |
| DALI | DALI (Comming soon) |

sales@biontechnologies.com
www.biontechnologies.com
Phone:
(DE) +49 8231 95787 0



All information without guarantee. Errors, changes and misprints excepted.